

Remote Particle Counter Model P235



The Airy Technology P235 remote particle counter measures 0.5 μm and 5.0 μm with a flow rate of 0.1 CFM (2.83 LPM). Integration is easy into a real-time monitoring or building management system via Modbus™ RTU or Modbus™ ASCII. The P235 is the smallest remote particle counter in the market and has easy mounting options. The Airy Technology P235 complies with ISO 21501-4 and includes a 2 year limited warranty.

Features & Benefits

- Measures 0.5 μm and 5.0 μm
- 0.1 CFM (2.83 LPM) flow rate
- Measures 2 channels of simultaneous data
- Long life laser diode
- Modbus™ RTU or ASCII outputs
- Concentration limit of 2,000,000 per ft^3
- Complies with ISO 21501-4 and JIS B9921 standards
- Lightweight stainless steel enclosure
- Easy to clean and wipe down
- 2 year limited warranty



CLEANROOM 
SYSTEMS GmbH 
Lösungen für die Reinraumtechnik

Tel.: +49 (0) 9181 904 33 63
Fax.: +49 (0) 9181 90433 89
www.cleanroom-systems.com
office@cleanroom-systems.com

Remote Particle Counter Model P235



Compact Size

CLEANROOM 
SYSTEMS GmbH 
Lösungen für die Reinraumtechnik

Tel.: +49 (0) 9181 904 33 63
Fax.: +49 (0) 9181 90433 89
www.cleanroom-systems.com
office@cleanroom-systems.com

Specifications

Channel Sizes	0.5 μm and 5.0 μm
Counting Efficiency	50% at 0.5 μm ; 100% for particles > 0.75 μm (per JIS)
Concentration Limits	2,000,000 particles / ft ³ at 5% coincidence loss
Light Source	Long life laser diode
Zero Count Level	<1 count / 5 minutes (per JIS B9921)
Flow Rate	0.1 CFM (2.83 LPM)
Flow Control	Critical orifice
Vacuum Requirements	External vacuum >15" (38.1 cm) of Hg
Calibration	NIST traceable
Sample Probe/Tubing	Isokinetic sampling probe
Communication Interface	Modbus™ RTU or ASCII outputs (specified upon order)
Power	9-30 VDC
Dimensions (L x W x H)	1.8" x 3.7" x 1.5" (4.5 cm x 9.3 cm x 3.8 cm) does not include probes
Weight	0.62 lb (0.28 kg)
Standards	ISO 21501-4 and JIS B9921
Warranty	2 year limited warranty
Operating Conditions	5° to 35°C 20% to 95%RH non-condensing
Storage Conditions	-20° to 50°C Up to 98%RH non-condensing
Optional Accessories	Isokinetic sampling probe, purge filter, data cable, vacuum and sample tubing



Airy Technology, Inc. reserves the right to change specifications without notice. Contact www.airytechnology.com or your local distributor for more details. Airy Technology and the Airy Technology logo are trademarks of Airy Technology, Inc. ©2014 Airy Technology, Inc. All rights reserved.



31 Tosca Drive
Stoughton, MA 02072 U.S.A.
781.341.1850 phone
hello@airytechnology.com
www.airytechnology.com